

HI-RESOLUTION INK JET PRINTER

JONECO Hr-200

Our JONECO HR-series inkjet printers are equipped with piezo print head technology, which enable to print in 180 DPI and improve the quality of your products and increase customer satisfaction.



Easy maintenance of print-head management (semi-permanent print-head), Non-contact printing for stable printing



Support USB port to Back Up/ Restore the data, image (Logo), using message list



User can easily editing the barcode manufacture date, expiration date, product ID, bar code, etc. in your controller by freely selecting small letters to large letters.

JONECO Hr-200

HI-RESOLUTION INK JET PRINTER

Specification

Model	JONECO Hr-200	JONECO Hr-500
Maximum print height	17 mm	70 mm
User Interface	Screen touch GUI	
Maximum printing speed	50m/min(80pl), 60m/min (40pl)	60m/min (75pl)
Distance (from Print-head)	Recommend: 1mm ~ 5mm	Recommend : 1mm~10mm
Quantity of print-head using	2EA	1EA
Type of Ink	Oil base ink (Only print on porous materials)	
Ink capacity	300cc, 500cc	
Communication	RS-232	
File system	USB (fat 16, fat 32)	
I/O Modules	Sensor, Encoder, Ex-in, Ex-out	
Font type	128F Dots 128 Dots, 96 Dots, 76 Dots, 64 Dots, 48 Dots, 32 Dots, 24 Dots, 16 Dots, OCR-B	
Print message type	English, Image(company's symbol), Barcode, Numeric	
Message storage	Up to 1000	
Print support (Display)	Manufacture date, Expiration date, Time, Count the number of print & lot & box, Julian date	
Printing method (Application)	Fixed & Variable Data, Up / Down Reverse, Repeat Print Delay Print, Encoder, Forward / Reverse	
Barcode	CODE 128A, CODE 128B, CODE 128C, CODE 128AUTO, Code 93, CODE 39, EAN 8, EAN 13, EAN 14, I 2 of 5, UPC-A, DATAMATRIX, GS1(DATAMATRIX), QR CODE	
Greyscale	N/A	6 Step
Display Language	KOREA, ENGLISH	
Operation Environment	10 ~ 35°C (Select Print-head heater option according to usage environment)	
Power Voltage	110V or 220V / 50,60Hz	



- Non-contact head-marking method of ink jet marking prevents print-head's damage due to external impact that can occur in printing



- User-friendly feature of the controller items



- Communication between PC and Controller for internal data

J-ONE CO., LTD.

2, Dangjeong-ro 60beonan-gil, Gunpo-si, Gyeonggi-do, Korea
 TEL : +82-31-458-9300 FAX : +82-31-458-0708 www.joneco.com
 E-mail : Help@joneco.com michael@joneco.com